

## 460SJi



### Optional 69KV Rating

	<b>460SJi</b>
<b>Specifications</b>	<b>US</b>
Working Height	52 ft
Platform Height	46 ft
Platform Capacity	500 lbs
Platform Size	24 x 48 in
Stowed Height	8 ft 5 in
Stowed Length	33 ft 6 in
Horizontal Reach	40 ft 6 in
Overall Width	7 ft 6.5 in
Tail Swing	2 ft 10 in
Ground Clearance	12.5 in
Turret Rotation	360°Continuous
Platform Rotation	180°
Power Source	GM Dual Fuel or Perkins Diesel Engine
Hydraulic Tank Capacity	42 gal
Fuel Tank Capacity	26 gal
Wheel Base	7 ft 8 in
Tire Size/Type Standard	12. x 16.5
Gross Weight (est)	15,855 lbs
Travel Speed	4.25 MPH
Gradeability 2WD/4WD	30%/45%
Turning Radius (Inside)	6 ft 7 in
TurningRadius(Outside)	16 ft 5 in

*Specifications Subject to Change without Prior Notice*

### STANDARD EQUIPMENT:

- 46' Platform Height
- 52' Working Height
- Horizontal Outreach 40' 6"
- Platform Size 24" x 48"
- Overall Width 7' 6"
- Stowed Height 8' 5"
- Stowed Length 33' 6"
- Ground Clearance 12.5"
- Proportional Hydraulic Controls
- Hydrostatic Drive
- 2/4 Wheel Drive
- Dual Fuel or Diesel Engine
- ANSI Category C 46kv insulating Package
  - 6ft Fiberglass Boom Tip
  - Fiberglass Bucket
  - Radio Remote Controls

**MLE**  
MAN & MATERIAL LIFT ENGINEERING

5707 S. Pennsylvania Avenue  
Cudahy, WI 53110  
Phone: 414-486-1760  
Fax: 414-486-1763  
[www.manliftengineering.com](http://www.manliftengineering.com)  
[sales@manliftengineering.com](mailto:sales@manliftengineering.com)