

I n s u l a t e d L i f t

660SJi



660SJi	
Specifications	US
Working Height	72 ft
Platform Height	66 ft
Platform Capacity	500 lbs
Platform Size	24 x 48 in
Stowed Height	8 ft 5 in
Stowed Length	33 ft 6 in
Horizontal Reach	56 ft 9 in
Overall Width	7 ft 11 in
Tail Swing	3 ft 9 in
Ground Clearance	12 in
Turret Rotation	360°Continuous
Platform Rotation	180°
Power Source	GM Dual Fuel or Deutz Diesel Engine
Hydraulic Tank Capacity	32 gal
Fuel Tank Capacity	40 gal
Wheel Base	8 ft 1 in
Tire Size /Type	15 x 19.5 Lug tread
Gross Weight (est)	27,600 lbs
Travel Speed	4.25 MPH
Gradeability 2WD/4WD	30%/45%
Turning Radius (Inside) 2WS /4WS	11 ft 4 in/5 ft 5 in
TurningRadius(Outside) 2WS,4WS	17 ft 9 in/11 ft 4 in

Specifications Subject to Change without Prior Notice

STANDARD EQUIPMENT:

- 66' Platform Height
- 72' Working Height
- Horizontal Outreach 75'
- Platform Size 24" x 48"
- Overall Width 7' 11"
- Stowed Height 8' 5"
- Stowed Length 33' 6"
- Ground Clearance 12"
- Proportional Hydraulic Controls
- Hydrostatic Drive
- 2/4 Wheel Drive
- Dual Fuel or Diesel Engine
- ANSI Category C 46kv insulating Package
 - 6ft Fiberglass Boom Tip
 - Fiberglass Bucket
 - Radio Remote Controls

MLE
MAN & MATERIAL LIFT ENGINEERING

5707 S. Pennsylvania Avenue
Cudahy, WI 53110
Phone: 414-486-1760
Fax: 414-486-1763
www.manliftengineering.com
sales@manliftengineering.com