

E X S e r i e s

Class I. Division 1 Hazardous Environment

A34EX



	A34EX	
	US	Metric
Working Height	40 ft 8 in	12.6 m
Platform height	34 ft 4 in	10.5 m
Horizontal Reach	22 ft 4 in	6.8 m
Up and Over Height	15 ft	4.6 m
Swing	355°	355°
Platform Rotation	160°	160°
Lift Capacity	500 Pounds	227 kg
Platform Size	56 x 30 in	1.42 x .76 m
Overall Height Stowed	7 ft 4 in	2.23 m
Overall Length Stowed	19 ft	5.79 m
Overall Width	5 ft 8 in	1.42 m
Wheelbase	6 ft 2 in	1.88 m
Ground Clearance	5.75 in	15 cm
Tailswing	Zero	Zero
Hydraulic Tank Capacity	18 Gal	68 L
Weight	12,000Pounds	5,442 kg
Drive Speed (Stowed)	2 MPH	
Gradeability	25%	25%
Tires	9-14.5 Industrial	9-14.5 Industrial
Turning Radius (Inside/Outside)	5 ft 8 in/13 ft 1in	1.73 m /4 m
Lifting Eyes	Yes	Yes
Max. Ground Bearing Pressure	185 psi	
Batteries	8 x 6V 370Amp-hr	
Charger	21 Amp, Automatic Charger	

STANDARD EQUIPMENT:

- 34' Platform Height
- 40' Working Height
- Horizontal Outreach 22' 4"
- Up and Over Height 15'
- Platform Size 30" X 56"
- Overall Width 5' 8"
- Stowed Height 7' 4"
- Stowed Length 19'
- Ground Clearance 5.75"
- Hydraulic Controls
- Designed in Accordance with NFPA 70 Class I, Division 1, Group D for Hazardous Environments

MLE
 MAN & MATERIAL LIFT ENGINEERING
 5707 S. Pennsylvania Avenue
 Cudahy, WI 53110
 Phone: 414-486-1760
 Fax: 414-486-1763
www.manliftengineering.com
sales@manliftengineering.com

