



1532EX EXPLOSION PROOF SCISSOR LIFT

SPECIFICATIONS	US	METRIC
Working Height	21 ft	6.4 m
Raised Platform Height	15 ft	4.6 m
Lowered Platform Height	34.5 in	.88 m
Platform Size (inside)	26 x 64 in	.66 x 1.6 m
Platform Capacity	600 lbs	227 kg
Overall Width	32 in	.81 m
Overall Length	89 in	2.26 m
Stowed Height	74 in	1.9 m
Deck Extension	3 ft	.91 m
Ground Clearance (Stowed)	2.375 in	6 cm
Ground Clearance (Raised)	.7 in	1.8 cm
Wheelbase	55 in	1.4 m
Inside Turning Radius	Zero	
Outside Turning Radius	66 in	1.68 m
Drive Speed (Stowed)	1 mph	1.6 km/h
Drive Speed (Raised)	.7 mph	1.1 km/h
Batteries	4 x 6V 232 Amp-hr	
Charger	20 Amp Automatic SCR	
Gradeability	25 %	

**Specifications Subject to Change Without Prior Notice*

1532EX

- **Explosion Proof**
- **Factory Mutual Approved**
- **Class I, Division 1, Group D**



STANDARD EQUIPMENT

- 15 ft. Platform Height
- 21 ft. Working Height
- 26 x 64 in. Platform Size
- 2.375 in. Ground Clearance
- 600 lb Platform Capacity
- 3 ft. Extendable Deck
- 250 lb Extendable Deck Lift Capacity
- Proportional Hydraulic Controls
- Battery Condition Indicator

OPTIONS

- 3-Way Bump Protection
- Movement Alarm
- 3/8" Airline to Platform
- 250 Amp Hr Battery & 40 Amp Charger