# 2646EX
## EXPLOSION PROOF SCISSOR LIFT

MAN & MATERIAL LIFT ENGINEERING

Made in USA

## 2646EX EXPLOSION PROOF SCISSOR LIFT

| SPECIFICATIONS | US | METRIC |
|---|---|---|
| Working Height | 32 ft | 9.8 m |
| Raised Platform Height | 26 ft | 7.9 m |
| Lowered Platform Height | 45 in | 1.1 m |
| Platform Size (inside) | 42 x 84 in | 1.1 x 2.1 m |
| Platform Capacity | 1000 lbs | 454 kg |
| Overall Width | 46 in | 1.2 m |
| Overall Length | 108 in | 2.75 m |
| Stowed Height | 84.5 in | 2.1 m |
| Deck Extension | 4 ft | 1.2 m |
| Ground Clearance (Stowed) | 3.5 in | 8.9 cm |
| Ground Clearance (Raised) | .75 in | 1.9 cm |
| Wheelbase | 69 in | 1.8 m |
| Inside Turning Radius | 47.5 in | 1.2 m |
| Outside Turning Radius | 93.5 in | 2.4 m |
| Drive Speed (Stowed) | 1 mph | 1.6 km/h |
| Drive Speed (Raised) | .6 mph | 1 km/h |
| Batteries | 4 x 6V 232 Amp-hr | |
| Charger | 20 Amp Automatic SCR | |
| Gradeability | 25 % | |
| | | |
| | | |
| | | |
| | | |

*Specifications Subject to Change Without Prior Notice*

## 2646EX

- **Explosion Proof**
- **Factory Mutual Approved**
- **Class I, Division 1, Group D**

EX

FM APPROVED

## STANDARD EQUIPMENT

- 26 ft. Platform Height
- 32 ft. Working Height
- 42 x 84 in. Platform Size
- 3.5 in. Ground Clearance
- 1000 lb Platform Capacity
- 4 ft. Extendable Deck
- Proportional Hydraulic Controls
- Battery Condition Indicator

## OPTIONS

- 3-Way Bump Protection
- Movement Alarm
- 3/8” Airline to Platform
- 6 ft. Powered Extendable Deck
- 250 Amp Hr Battery & 40 Amp Charger