



3188EX EXPLOSION PROOF SCISSOR LIFT

SPECIFICATIONS	US	METRIC
Working Height	37 ft	11.3 m
Raised Platform Height	31 ft	9.4 m
Lowered Platform Height	59 in	1.5 m
Platform Size (inside)	67 x 134 in	1.7 x 3.4 m
Platform Capacity	2000 lbs	907 kg
Overall Width	87 in	2.42 m
Overall Length	147 in	3.73 m
Stowed Height	105 in	2.7 m
Deck Extension	4 ft	1.2 m
Ground Clearance (Stowed)	8 in	20.3 cm
Ground Clearance (Raised)	.7 in	1.8 cm
Wheelbase	89.3 in	2.3 m
Inside Turning Radius	158 in	4.0 m
Outside Turning Radius	248 in	6.3 m
Drive Speed (Stowed)	1 mph	1.6 km/h
Drive Speed (Raised)	.6 mph	1.0 km/h
Batteries	8 x 6V 420 Amp-hr	
Charger	21 Amp Automatic SCR	
Gradeability	30 %	

*Specifications Subject to Change Without Prior Notice

3188EX

- Explosion Proof
- Class I, Division 1, Group D

STANDARD EQUIPMENT

- 31 ft. Platform Height
- 37 ft. Working Height
- 67 x 134 in. Platform Size
- 8 in. Ground Clearance
- 2000 lb Platform Capacity
- 4 ft. Extendable Deck
- Proportional Hydraulic Controls
- Battery Condition Indicator

OPTIONS

- 3-Way Bump Protection
- Movement Alarm
- 3/8" Airline to Platform
- 4 ft. Powered Extendable Deck
- Dual 4 ft. Roll-out or Powered Extendable Decks
- 250 Amp Hr Battery & 40 Amp Charger