MLE

3246EX
EXPLOSION PROOF SCISSOR LIFT

MAN & MATERIAL LIFT ENGINEERING

Made in USA

3246EX EXPLOSION PROOF SCISSOR LIFT

SPECIFICATIONS	US	METRIC
Working Height	38 ft	11.6 m
Raised Platform Height	32 ft	9.8 m
Lowered Platform Height	48.5 in	1.2 m
Platform Size (inside)	42 x 84 in	1.1 x 2.1 m
Platform Capacity	700 lbs	318 kg
Overall Width	46 in	1.2 m
Overall Length	108 in	2.75 m
Stowed Height	88 in	2.2 m
Deck Extension	4 ft	1.2 m
Ground Clearance (Stowed)	3.5 in	8.9 cm
Ground Clearance (Raised)	.75 in	1.9 cm
Wheelbase	69 in	1.8 m
Inside Turning Radius	47.5 in	1.2 m
Outside Turning Radius	93.5 in	2.4 m
Drive Speed (Stowed)	1 mph	1.6 km/h
Drive Speed (Raised)	.6 mph	1 km/h
Batteries	4 x 6V 232 Amp-hr	
Charger	19 Amp Automatic SCR	
Gradeability	25 %	

Specifications Subject to Change Without Prior Notice

3246EX

- **Explosion Proof**
- **Factory Mutual Approved**
- **Class I, Division 1, Group D**

EX

FM APPROVED

STANDARD EQUIPMENT

- 32 ft. Platform Height
- 38 ft. Working Height
- 42 x 84 in. Platform Size
- 3.5 in. Ground Clearance
- 700 lb Platform Capacity
- 4 ft. Extendable Deck
- Proportional Hydraulic Controls
- Battery Condition Indicator

OPTIONS

- 3-Way Bump Protection
- Movement Alarm
- 3/8” Airline to Platform
- 6 ft. Powered Extendable Deck
- 250 Amp Hr Battery & 40 Amp Charger