



### 4188EX EXPLOSION PROOF SCISSOR LIFT

SPECIFICATIONS	US	METRIC
Working Height	47 ft	14.3 m
Raised Platform Height	41 ft	12.5 m
Lowered Platform Height	69 in	1.8 m
Platform Size (inside)	67 x 134 in	1.7 x 3.4 m
Platform Capacity	1500 lbs	680 kg
Overall Width	87 in	2.2 m
Overall Length	147 in	3.73 m
Stowed Height	114 in	2.9 m
Deck Extension	4 ft	1.22 m
Ground Clearance (Stowed)	8 in	20.3 cm
Ground Clearance (Raised)	.7 in	1.9 cm
Wheelbase	89.3 in	2.3 m
Inside Turning Radius	158 in	4.0 m
Outside Turning Radius	248 in	6.3 m
Drive Speed (Stowed)	1 mph	1.6 km/h
Drive Speed (Raised)	.6 mph	1.0 km/h
Batteries	8 x 6V 420 Amp-hr	
Charger	21 Amp Automatic SCR	
Gradeability	30 %	

\*Specifications Subject to Change Without Prior Notice

### 4188EX

- Explosion Proof
- Class I, Division 1, Group D

### STANDARD EQUIPMENT

- 41 ft. Platform Height
- 47 ft. Working Height
- 67 x 134 in. Platform Size
- 8 in. Ground Clearance
- 1500 lb Platform Capacity
- 4 ft. Extendable Deck
- Proportional Hydraulic Controls
- Battery Condition Indicator

### OPTIONS

- 3-Way Bump Protection
- Movement Alarm
- 3/8" Airline to Platform
- 4 ft. Powered Extendable Deck
- Dual 4 ft. Roll-out or Powered Extendable Decks
- 250 Amp Hr Battery & 40 Amp Charger