



### 5092EX EXPLOSION PROOF SCISSOR LIFT

| SPECIFICATIONS            | US                   | METRIC      |
|---------------------------|----------------------|-------------|
| Working Height            | 56 ft                | 17.1 m      |
| Raised Platform Height    | 50 ft                | 15.2 m      |
| Lowered Platform Height   | 79 in                | 2.0 m       |
| Platform Size (inside)    | 74 x 168 in          | 1.9 x 4.3 m |
| Platform Capacity         | 2000 lbs             | 907 kg      |
| Overall Width             | 92 in                | 2.3 m       |
| Overall Length            | 176 in               | 4.5 m       |
| Stowed Height             | 124.5 in             | 3.2 m       |
| Deck Extension            | 5 ft                 | 1.5 m       |
| Ground Clearance (Stowed) | 8 in                 | 20.3 cm     |
| Ground Clearance (Raised) | .7 in                | 1.9 cm      |
| Wheelbase                 | 119 in               | 3.0 m       |
| Inside Turning Radius     | 210 in               | 5.3 m       |
| Outside Turning Radius    | 301 in               | 7.7 m       |
| Drive Speed (Stowed)      | 1 mph                | 1.6 km/h    |
| Drive Speed (Raised)      | .6 mph               | 1 km/h      |
| Batteries                 | 8 x 6V 420 Amp-hr    |             |
| Charger                   | 21 Amp Automatic SCR |             |
| Gradeability              | 30 %                 |             |
|                           |                      |             |
|                           |                      |             |
|                           |                      |             |
|                           |                      |             |
|                           |                      |             |

\*Specifications Subject to Change Without Prior Notice

### 5092EX

- Explosion Proof
- Class I, Division 1, Group D

### STANDARD EQUIPMENT

- 50 ft. Platform Height
- 56 ft. Working Height
- 74 x 168 in. Platform Size
- 8 in. Ground Clearance
- 2000 lb Platform Capacity
- Proportional Hydraulic Controls
- Battery Condition Indicator
- Disc Brake System on Rear Axle
- Independent Leveling Hydraulic Outriggers

### OPTIONS

- 3-Way Bump Protection
- Movement Alarm
- 3/8" Airline to Platform
- 5 ft. Powered Extendable Deck
- Dual 4 ft. Roll-out or Powered Extendable Decks
- Remote Mount 600 Amp Charger & Battery