

VM36EX-DC

Class I, Division 1, Hazardous Environment



Specifications	VM36EX-DC	
Platform Height - Raised	29 ft 10 in	9.09 m
Platform Height - Lowered	19 in	48 cm
Platform Railing Height	3 ft 7.5 in	1.1 m
Platform Size	26 x 25.5 in	66 cm x 65 cm
Platform Extension	3 ft	.91 m
Overall Height-Stowed	77.5 in	1.97 m
Overall Width	29 in	74 cm
Overall Length	64 in	1.63 m
Overall Length- Without Platform	59 in	1.50 m
Outrigger Footprint Length	68 in	1.73 m
Outrigger Footprint Width	61 in	1.55 m
Distance to Wall-Front	5 in	13 cm
Distance to Wall-Side	18 in	44 cm
Platform Capacity	350 lbs	159 kg
Gross Weight	1,960 lb	889 kg
Rear Wheels	10 in x 2 in	25 cm x 5 cm
Front Caster Wheels	6 in x 2 in	15 cm x 5 cm
Batteries	4 x 6V 220 Amp-hr	

STANDARD EQUIPMENT:

- **Low Maintenance Anodized Mast**
- **Auto Power Saver - Shuts Off Power When Idle**
- **Lanyard Attachment Anchor for Body Harness**
- **Non-Marking Tires**
- **Quick-Change Platform Mounts**
- **Quick-Change 28 x 26 in. (71 x 66 cm) - Gull Wing Entry Platform**
- **Automatic Battery Charger**
- **Battery Discharge Indicator (BDI)**
- **Roller Loading Device For Loading On Standard Size Pick Up Trucks**
- **Designed in Accordance to NFPA 70 Class I, Division 1, Group D**



5707 S. Pennsylvania Avenue
 Cudahy, WI 53110
 Phone: 414-486-1760
 Fax: 414-486-1763
www.manliftengineering.com
sales@manliftengineering.com